

## NEUTRAL CONDITIONER FOR COATED WOODEN FLOORING - DEOLUX

**Neutral liquid conditioner. Protects wooden floors against wear and creates a dust-proof, anti-static surface.**

---

### INTENDED USES

Coated wooden flooring for interiors.

---

### APPLICATION

- Carefully wash the floor to be treated, using PULIWOOD detergent.
  - To revitalize the wooden flooring from time to time, dilute the product (250 ml for every 5 liters of water) and apply using the appropriate microfiber cloth.
  - To treat particularly worn wooden floors, apply the product without dilution, using the appropriate microfiber cloth, taking care to dampen the cloth first.
  - In both cases, the product should be spread evenly across the entire surface, avoiding build-ups.
- 



Interior use



Dilution  
with water



Application  
with cloth

---

### CHEMICAL/PHYSICAL CHARACTERISTICS

Specific weight: 1.00 ± 0.05 g/ml

---

### POINTS TO NOTE

Keep from freezing. Store at temperatures between 5°C and 35°C.

Mix well before use.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Dispose of contents and container in accordance with local, regional, international regulations.

---

### SAFETY RECOMMENDATIONS

Consult the product's Safety Data Sheet (SDS), which can be downloaded from the [www.icaforyou.com](http://www.icaforyou.com) website.

---

The user must first ensure the suitability of the product for the specific intended use. We accept no responsibility for the outcome of the processing operations. The information contained on this technical data sheet, and any verbal information that may be provided, is supplied to the best of our knowledge. No liability is accepted for obsolete or incorrect information. The information on this technical data sheet is rendered obsolete upon publication of a new edition. Contact us to receive the latest edition or download it from the [www.icaforyou.com](http://www.icaforyou.com) website.

---