

CLEAR WATER-BASED WOOD FINISH - FNTXX

Odorless and with low environmental impact. Easy to apply by brush or spray, onto pre-stained wood. Protects the wood against weathering and UV rays.

SHEEN

FNT35 MATT NEUTRAL

FNT60 SEMI-GLOSS NEUTRAL

INTENDED USES

Wood frames, shutters, fences, balconies and other wood items located outdoors, beams and attics.

APPLICATION

USE ON NEW WOOD

- The wood must be clean and dry, free of dust, oily residues or products that can limit adhesion.
- Sand with 150/180-grain sandpaper, apply a coat of IMG-series exterior wood stain and leave to dry.
- Mix the product thoroughly and apply it with a brush (with synthetic bristles).
- After 2–4 hours apply the second coat of product.

USE ON COATED WOOD

- Sand with 100/120-grain sandpaper until the complete removal of the pre-existing coating.
- Complete the sanding with 150/180-grain sandpaper and apply a coat of IMG-series exterior wood stain.
- Mix the product thoroughly and apply it with a brush (with synthetic bristles).
- Proceed as stated above for use on new wood.
- On wood previously treated with the same product, which has not yet degraded, clean the surface, sand lightly with 180-grain sandpaper, remove the sawdust and proceed with application of the product.



Interior and exterior use



Ready to use



Brush or spray application



Tool cleaning with water



Coverage 9-12 m²/L per coat



Dries completely in 24 hours

CHEMICAL/PHYSICAL CHARACTERISTICS

Specific weight: 1.04±0.05 g/ml

Viscosity: 110±10 sec. C. ISO 6

WARNINGS

Keep from freezing. Store at temperatures between 5°C and 35°C.

Mix well before use.

Apply at a temperature above 10°C with relative humidity below 75%; temperature and humidity influence the stated drying times.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Dispose of contents and container in accordance with local, regional, international regulations.

Technical Data Sheet

NOTES

Complies with the VOC (Volatile Organic Compound) limits set by the Decopaint Directive (Directive 2004/42/CE).

SAFETY RECOMMENDATIONS

Consult the product's Safety Data Sheet (SDS), which can be downloaded from www.icaforyou.com website.

The user must first ensure the suitability of the product for the specific intended use. We accept no responsibility for the outcome of the processing operations. The information contained on this technical data sheet, and any verbal information that may be provided, is supplied to the best of our knowledge. No liability is accepted for obsolete or incorrect information. The information on this technical data sheet is rendered obsolete upon publication of a new edition. Contact us to receive the latest edition or download it from the www.icaforyou.com website.
