

## CLEAR WATER-BASED WOOD PRIMER AND FINISH – FFTXX

**Odorless and with low environmental impact. Easy to apply by brush without dripping, it protects the wood against scratches and stains. Can be washed with neutral detergents.**

### SHEEN

FFT20 SATIN

FFT60 SEMI-GLOSS

### INTENDED USES

Wood furniture and items for indoors (chairs, doors, tables, kitchen-cabinet doors, baseboards/skirting, etc.).

### APPLICATION

#### USE ON NEW WOOD

- The wood must be clean and dry, free from dust, oily residues or products that may limit adhesion.
- Sand the surface using 150/180-grain sandpaper.
- Mix the product thoroughly and apply it with a brush (with synthetic bristles).
- Within 4 hours, if necessary apply a second coat of product, without sanding, leave to dry for at least 4–6 hours, after which sand with 280/320-grain sandpaper, before applying the final coat.

#### USE ON COATED WOOD

- Sand the surface using 100/120-grain sandpaper until the complete removal of the pre-existing coating.
- Complete the sanding with 150/180-grain sandpaper.
- Remove the sawdust.
- Mix the product thoroughly and apply it with a brush (with synthetic bristles).
- Proceed as stated above for use on new wood.



Interior use



Ready to use



Brush or spray application



Tool cleaning with water



Coverage 10-12 m<sup>2</sup>/L per coat



Final drying 12-24 hours

### CHEMICAL/PHYSICAL CHARACTERISTICS

Specific weight:

1.03 ± 0.05 g/ml

Viscosity:

120 ± 20 sec. DIN 4

### WARNINGS

Keep from freezing. Store at temperatures between 5°C and 35°C.

Mix well before use.

Apply at a temperature above 10°C with relative humidity below 75%; temperature and humidity influence the stated drying times.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Dispose of contents and container in accordance with local, regional, international regulations.



# Technical Data Sheet

---

## **NOTES**

Complies with the VOC (Volatile Organic Compound) limits set by the Decopaint Directive (Directive 2004/42/CE).

---

## **SAFETY RECOMMENDATIONS**

Consult the product's Safety Data Sheet (SDS), which can be downloaded from the [www.icaforyou.com](http://www.icaforyou.com) website.

---

The user must first ensure the suitability of the product for the specific intended use. We accept no responsibility for the outcome of the processing operations. The information contained on this technical data sheet, and any verbal information that may be provided, is supplied to the best of our knowledge. No liability is accepted for obsolete or incorrect information. The information on this technical data sheet is rendered obsolete upon publication of a new edition. Contact us to receive the latest edition or download it from the [www.icaforyou.com](http://www.icaforyou.com) website.

---