

## CLEAR HIGH-TRAFFIC WATER-BASED COATING - VPAXX

**Odorless and with low environmental impact. Easy to apply by roller, it protects wood against scratches and staining. Can be washed with neutral detergents.**

---

### SHEEN

VPA05 EXTRA-MATT

VPA60 SEMI-GLOSS

---

### INTENDED USES

Wood floors for interiors.

---

### APPLICATION

#### USE ON NEW WOOD

- The wood must be clean and dry, free of dust, oily residues or products that can limit adhesion.
- Sand the surface using 150/180-grain sandpaper.
- Mix the product thoroughly and apply using a roller (specifically designed for water-based coatings).
- Leave to dry for at least 3 hours, then sand carefully with 220/320-grain sandpaper.
- Apply the second coat.
- Leave to dry for at least 16 hours.
- Sand with 280/320-grain sandpaper, remove the sawdust and then apply the final coat.

#### USE ON COATED WOOD

- Sand with 100/120-grain sandpaper until the complete removal of the pre-existing coating.
  - Complete the sanding with 150/180-grain sandpaper.
  - Remove the sawdust.
  - Mix the product thoroughly and apply using a roller (specifically designed for water-based coatings).
  - Proceed as stated above for use on new wood.
- 



Interior use



Ready to use



Roller application



Tool cleaning  
with water



Coverage 10-12 m<sup>2</sup>/L  
per coat



Can be walked on  
after 24 hours

---

### CHEMICAL/PHYSICAL CHARACTERISTICS

Specific weight:

VPA05: 1.05 ± 0.05 g/ml

VPA60: 1.03 ± 0.05 g/ml

Viscosity:

VPA05: 60 ± 5 sec. C. FORD 2

VPA60: 45 ± 5 sec. C. FORD 2

---

### WARNINGS

Keep from freezing. Store at temperatures between 5°C and 35°C.

Mix well before use.

Apply at a temperature of between 10°C and 30°C, with relative humidity below 75%; temperature and humidity influence the stated drying times.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Dispose of contents and container in accordance with local, regional, international regulations.

---



# Technical Data Sheet

---

## **NOTES**

Complies with the VOC (Volatile Organic Compound) limits set by the Decopaint Directive (Directive 2004/42/CE).

---

## **SAFETY RECOMMENDATIONS**

Consult the product's Safety Data Sheet (SDS), which can be downloaded from the [www.icaforyou.com](http://www.icaforyou.com) website.

---

The user must first ensure the suitability of the product for the specific intended use. We accept no responsibility for the outcome of the processing operations. The information contained on this technical data sheet, and any verbal information that may be provided, is supplied to the best of our knowledge. No liability is accepted for obsolete or incorrect information. The information on this technical data sheet is rendered obsolete upon publication of a new edition. Contact us to receive the latest edition or download it from the [www.icaforyou.com](http://www.icaforyou.com) website.

---