



Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **FFT20**
Product name: **TRANSPARENT WATER BASED FROSTED BASE/TOP COAT FOR WOOD**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Paint product**

1.3. Details of the supplier of the safety data sheet

Name: **ICA S.p.A.**
Full address: **Via S. Pertini, 52**
District and Country: **62012 Civitanova Marche (MC) ITALY**
Tel.: **+39 0733 8080**
Fax: **+39 0733 808140**

e-mail address of the competent person responsible for the Safety Data Sheet: **regulatoryaffairs@icaspa.com**

Product distribution by: **INDUSTRIA CHIMICA ADRIATICA S.p.A.**

1.4. Emergency telephone number

For urgent inquiries refer to: **Centro antiveleni – Ospedale di Firenze (24/24 h)**
Telefono: +39 055 794 7819

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.
EUH208 Contains: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
2,4,7,9-tetramethyldec-5-yne-4,7-diol
May produce an allergic reaction.

Precautionary statements: --

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.



SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
Dipropylene glycol monomethyl ether		
CAS	34590-94-8	1,5 ≤ x < 2
EC	252-104-2	
INDEX		
Reg. no.	01-2119450011-60-XXXX	
2-butoxyethanol		
CAS	111-76-2	0,6 ≤ x < 0,7
EC	203-905-0	
INDEX	603-014-00-0	
Reg. no.	01-2119475108-36-XXXX	
Ethanolamine		
CAS	141-43-5	0,05 ≤ x < 0,1
EC	205-483-3	
INDEX	603-030-00-8	
Reg. no.	01-2119486455-28-XXXX	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.



SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Store at temperatures between 5°C and 35°C.

7.3. Specific end use(s)

See paragraph 1.2. For further information consult the technical data sheet.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK nr 655 af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL- OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 10/2018
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

SECTION 8. Exposure controls/personal protection ... / >>

GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM–SZCSM együttes rendelet módosításáról
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
LTU	Lietuva	LIETUVOS HIGIENOS NORMA HN 23:2011 „CHEMINIŲ MEDŽIAGŲ PROFESINIO POVEIKIO RIBINIAI DYDŽIAI. MATAVIMO IR POVEIKIO VERTINIMO BENDRIEJI REIKALAVIMAI. Nr. V-695/A1-272, 2018-06-12, paskelbta TAR 2018-06-15, i. k. 2018-09988
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVK	Slovensko	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Uradni list Republike Slovenije 04.12.2018 - Uradnem listu RS št. 78 -PRAVILNIK o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
TUR	Türkiye	KİMYASAL MADDELERLE ÇALIŞMALARDA SAĞLIK VE GÜVENLİK ÖNLEMLERİ HAKKINDA YÖNETMELİK - Resmi Gazete Tarihi: 12.08.2013 Resmi Gazete Sayısı: 28733
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

SECTION 8. Exposure controls/personal protection ... / >>
Dipropylene glycol monomethyl ether
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	308	50			SKIN
TLV	CZE	270	44,55	550	90,75	SKIN
AGW	DEU	310	50	310	50	
MAK	DEU	310	50	310	50	
TLV	DNK	309	50			SKIN E
VLA	ESP	308	50			SKIN
HTP	FIN	310	50			SKIN
VLEP	FRA	308	50			SKIN
WEL	GBR	308	50			SKIN
TLV	GRC	600	100	900	150	
GVI/KGVI	HRV	308	50			SKIN
AK	HUN	308				
VLEP	ITA	308	50			SKIN
RD	LTU	300	50	450	75	SKIN
TGG	NLD	300				
TLV	NOR	300	50			SKIN
NDS/NDSch	POL	240		480		SKIN
VLE	PRT	308	50			SKIN
TLV	ROU	308	50			SKIN
NPEL	SVK	308	50			SKIN
MV	SVN	308	50			SKIN
ESD	TUR	308	50			SKIN
OEL	EU	308	50			SKIN
TLV-ACGIH		606	100	909	150	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	19	mg/l
Normal value in marine water	1,9	mg/l
Normal value for fresh water sediment	70,2	mg/kg
Normal value for marine water sediment	7,02	mg/kg
Normal value for the terrestrial compartment	2,74	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			VND	3,2 mg/m3			VND	310 mg/m3
Skin							VND	65 mg/kg bw/d

2-butoxyethanol
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	DNK	98	20	196	40	
TLV	NOR	50	10			
OEL	EU	98	20	246	50	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	8,8	mg/l
Normal value in marine water	0,88	mg/l
Normal value for fresh water sediment	34,6	mg/kg
Normal value for marine water sediment	3,46	mg/kg
Normal value for the terrestrial compartment	3,13	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	3,2 mg/kg				
Inhalation			VND	49 mg/m3			VND	98 mg/m3
Skin			VND	38 mg/kg			VND	75 mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

Ethanolamine

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	BGR	2,5	1	7,6	3	SKIN
TLV	CZE	2,5	1,0025	7,5	3,0075	
AGW	DEU	0,5	0,2	0,5	0,2	SKIN
MAK	DEU	0,51	0,2	0,51	0,2	
TLV	DNK	2,5	1			SKIN E
VLA	ESP	2,5	1	7,5	3	SKIN
HTP	FIN	2,5	1	7,6	3	SKIN
VLEP	FRA	2,5	1	7,6	3	SKIN
WEL	GBR	2,5	1	7,6	3	SKIN
TLV	GRC	2,5	1	7,6	3	
GVI/KGVI	HRV	2,5	1	7,6	3	SKIN
AK	HUN	2,5		7,6		SKIN
VLEP	ITA	2,5	1	7,6	3	SKIN
RD	LTU	2,5	1	7,6	3	SKIN
TGG	NLD	2,5		7,6		SKIN
TLV	NOR	2,5	1			SKIN
NDS/NDSch	POL	2,5		7,5		SKIN
VLE	PRT	2,5	1	7,6	3	SKIN
TLV	ROU	2,5	1	7,6	3	SKIN
NPEL	SVK	2,5	1	7,6	3	SKIN
MV	SVN	2,5	1	7,6	3	SKIN
OEL	EU	2,5	1	7,6	3	SKIN
TLV-ACGIH		7,5	3	15	6	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
 VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
------------	-------	-------------

**SECTION 9. Physical and chemical properties** ... / >>

Appearance	liquid
Colour	transparent
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not applicable
Relative density	1,03
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Total solids (250°C / 482°F)	33,37 %		
VOC (Directive 2010/75/EC) :	4,87 %	- 50,19	g/litre
VOC (volatile carbon) :	2,71 %	- 27,89	g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

Dipropylene glycol monomethyl ether
Forms peroxides with: air.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

Dipropylene glycol monomethyl ether
May react violently with: strong oxidising agents.

Ethanolamine

May react dangerously with: acrylonitrile, chloroepoxypropane, chlorosulphuric acid, hydrogen chloride, iron-sulphur compounds, acetic acid, acetic anhydride, mesityl oxide, nitric acid, sulphuric acid, strong acids, vinyl acetate, cellulose nitrate.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

Dipropylene glycol monomethyl ether
Avoid exposure to: sources of heat. Possibility of explosion.

Ethanolamine

Avoid exposure to: air, sources of heat.

10.5. Incompatible materials

Ethanolamine

Incompatible with: iron, strong acids, strong oxidants.

10.6. Hazardous decomposition products

Ethanolamine

May develop: nitric oxide, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	Not classified (no significant component)
LD50 (Oral) of the mixture:	Not classified (no significant component)
LD50 (Dermal) of the mixture:	Not classified (no significant component)

2-butoxyethanol	
LD50 (Oral)	1746 mg/kg Rat
LD50 (Dermal)	6411 mg/kg Pig
LC50 (Inhalation)	450 ppm Rat

Dipropylene glycol monomethyl ether	
LD50 (Oral)	> 5000 mg/kg Rat
LD50 (Dermal)	9510 mg/kg Rabbit
LC50 (Inhalation)	> 275 ppm Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)
2,4,7,9-tetramethyldec-5-yne-4,7-diol

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class



SECTION 11. Toxicological information ... / >>

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

2-butoxyethanol	
LC50 - for Fish	1474 mg/l/96h Fish
EC50 - for Crustacea	1550 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	911 mg/l/72h Algae

Dipropylene glycol monomethyl ether	
LC50 - for Fish	> 1000 mg/l/96h
EC50 - for Crustacea	1919 mg/l/48h
Chronic NOEC for Algae / Aquatic Plants	969 mg/l

12.2. Persistence and degradability

2-butoxyethanol
Rapidly degradable

Dipropylene glycol monomethyl ether	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

Ethanolamine	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

Dipropylene glycol monomethyl ether	
Partition coefficient: n-octanol/water	0,0043

Ethanolamine	
Partition coefficient: n-octanol/water	-2,3

12.4. Mobility in soil

Ethanolamine	
Partition coefficient: soil/water	-0,5646

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available



SECTION 15. Regulatory information ... / >>

Substances subject to the Stockholm Convention:
None

Healthcare controls
Information not available

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)
WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament



SECTION 16. Other information ... / >>

2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 07 / 08 / 09 / 10 / 11 / 12 / 15 / 16.

Changed TLVs in section 8.1 for following countries:

BGR, CZE, DEU, DNK, ESP, FIN, FRA, GBR, GRC, HRV, HUN, ITA, LTU, NLD, NOR, POL, PRT, ROU, SVK, SVN, TUR, TLV-ACGIH,