



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 1/15

Replaced revision:7 (Dated: 27/04/2020)

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: PULIWOOD
Product name: PULIWOOD NEUTRAL DETERGENT FOR COATED WOODEN FLOORING

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Paint or related material

1.3. Details of the supplier of the safety data sheet

Name: ICA S.p.A.
Full address: Via S. Pertini, 52
District and Country: 62012 Civitanova Marche (MC)
ITALY
Tel. +39 0733 8080
Fax +39 0733 808140
e-mail address of the competent person responsible for the Safety Data Sheet: regulatoryaffairs@icaspa.com
Product distribution by: INDUSTRIA CHIMICA ADRIATICA S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to:
Centro antiveneni –
Ospedale di Firenze (24/24 h)
Telefono: +39 055 794 7819

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.
Hazard classification and indication:

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 2/15

Replaced revision:7 (Dated: 27/04/2020)

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

Precautionary statements:

--

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
Isopropanol		
CAS 67-63-0	$1,5 \leq x < 2$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC 200-661-7		
INDEX 603-117-00-0		
Reg. no. 01-2119457558-25-XXXX		
Dipropylene glycol monomethyl ether		
CAS 34590-94-8	$1 \leq x < 1,5$	Substance with a community workplace exposure limit.
EC 252-104-2		
INDEX -		
Reg. no. 01-2119450011-60-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 3/15

Replaced revision:7 (Dated: 27/04/2020)

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 4/15

Replaced revision:7 (Dated: 27/04/2020)

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK nr 655 af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL- OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 10/2018
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM-SZCSM együttes rendelet módosításáról
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
LTU	Lietuva	Lietuvos higienos norma HN 23:2011 „CHEMINIŲ MEDŽIAGŲ PROFESINIO POVEIKIO RIBINIAI DYDŽIAI. MATAVIMO IR POVEIKIO VERTINIMO BENDRIEJI REIKALAVIMAI. Nr. V-695/A1-272, 2018-06-12, paskelbta TAR 2018-06-15, i. k. 2018-09988
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 5/15

Replaced revision:7 (Dated: 27/04/2020)

PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018 HOTĂRĂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov Uradni list Republike Slovenije 04.12.2018 - Uradnem listu RS št. 78 -PRAVILNIK o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu KİMYASAL MADDELERLE ÇALIŞMALARDA SAĞLIK VE GÜVENLİK ÖNLEMLERİ HAKKINDA YÖNETMELİK - Resmi Gazete Tarihi: 12.08.2013 Resmi Gazete Sayısı: 28733 Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC. ACGIH 2019
ROU	România	
SVK	Slovensko	
SVN	Slovenija	
TUR	Türkiye	
EU	OEL EU TLV-ACGIH	

**Isopropanol
Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	980		1225		
TLV	CZE	500	203,5	1000	407	
AGW	DEU	500	200	1000	400	
MAK	DEU	500	200	1000	400	
TLV	DNK	490	200			
VLA	ESP	500	200	1000	400	
VLEP	FRA			980	400	
WEL	GBR	999	400	1250	500	
TLV	GRC	980	400	1225	500	
GVI/KGVI	HRV	999	400	1250	500	
AK	HUN	500		2000		SKIN
RD	LTU	350	150	600	250	
TGG	NLD	650				
TLV	NOR	245	100			
NDS/NDSCh	POL	900		1200		SKIN
TLV	ROU	200	81	500	203	
NPEL	SVK	500	200	1000	400	
MV	SVN	500	200	2000	800	
TLV-ACGIH		492	200	983	400	

Predicted no-effect concentration - PNEC

Normal value in fresh water	140,9	mg/l
Normal value in marine water	140,9	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	26 mg/kg				



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 7/15

Replaced revision:7 (Dated: 27/04/2020)

Inhalation	VND	3,2 mg/m ³	VND	310 mg/m ³
Skin			VND	65 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	light blue
Odour	characteristic



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 8/15

Replaced revision:7 (Dated: 27/04/2020)

Odour threshold	Not available
pH	7,000
Melting point / freezing point	Not available
Initial boiling point	> 100 °C
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	> 1,0000
Relative density	0,98
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Total solids (250°C / 482°F)	0,33 %
VOC (Directive 2010/75/EC) :	3,18 % - 31,19 g/litre
VOC (volatile carbon) :	1,90 % - 18,58 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Dipropylene glycol monomethyl ether

Forms peroxides with: air.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 9/15

Replaced revision:7 (Dated: 27/04/2020)

The vapours may also form explosive mixtures with the air.

Dipropylene glycol monomethyl ether

May react violently with: strong oxidising agents.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Dipropylene glycol monomethyl ether

Avoid exposure to: sources of heat.Possibility of explosion.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 10/15

Replaced revision:7 (Dated: 27/04/2020)

LC50 (Inhalation) of the mixture:
Not classified (no significant component)
LD50 (Oral) of the mixture:
Not classified (no significant component)
LD50 (Dermal) of the mixture:
Not classified (no significant component)

Dipropylene glycol monomethyl ether

LD50 (Oral) > 5000 mg/kg Rat

LD50 (Dermal) 9510 mg/kg Rabbit

LC50 (Inhalation) > 275 ppm Rat

Isopropanol

LD50 (Oral) 4710 mg/kg Rat

LD50 (Dermal) 12800 mg/kg Rat

LC50 (Inhalation) 72,6 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 11/15

Replaced revision:7 (Dated: 27/04/2020)

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Dipropylene glycol monomethyl ether	
LC50 - for Fish	> 1000 mg/l/96h
EC50 - for Crustacea	1919 mg/l/48h
Chronic NOEC for Algae / Aquatic Plants	969 mg/l
Isopropanol	
LC50 - for Fish	> 100 mg/l/96h Fish
EC50 - for Crustacea	260 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h Algae

12.2. Persistence and degradability

Dipropylene glycol monomethyl ether	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

Isopropanol
Rapidly degradable

12.3. Bioaccumulative potential

Dipropylene glycol monomethyl ether	
Partition coefficient: n-octanol/water	0,0043



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 12/15

Replaced revision:7 (Dated: 27/04/2020)

Isopropanol

Partition coefficient: n-octanol/water 0,05

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 13/15

Replaced revision:7 (Dated: 27/04/2020)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 14/15

Replaced revision:7 (Dated: 27/04/2020)

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization



ICA S.p.A.

Revision nr. 8

Dated 07/05/2020
Printed on 13/05/2020

**PULIWOOD - PULIWOOD NEUTRAL
DETERGENT FOR COATED WOODEN
FLOORING**

Page n. 15/15

Replaced revision:7 (Dated: 27/04/2020)

- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 05 / 08 / 09 / 10 / 11 / 12 / 15 / 16.