

## ARDESYA CHALKBOARD-EFFECT WATER-BASED PAINT – ADY00

**Odorless and with low environmental impact. Easy to apply by spraying or with a brush on wood or walls. It dries rapidly. It allows for writing with chalk and erasing with a dry or wet cloth, like on conventional slate blackboards.**

### COLORS

ADY00 BLACK

### INTENDED USES

Wood furnishings and complementary furnishings for interiors and indoor walls.

### APPLICATION

#### USE ON NEW WOOD

- The wood must be clean and dry, free of dust, oily residues or products that can limit adhesion.
- Sand the surface using 150/180-grit sandpaper.
- Mix the product thoroughly and apply it with a brush (with synthetic bristles) or roller. If the product is applied by spraying, it should be diluted with water up to 10% by weight.
- A single coat is sufficient to obtain full coverage. A second coat of the product can be applied 1–4 hours after the first coat.

#### USE ON COATED WOOD

- Sand the surface using 280/320-grit sandpaper and remove the sawdust.
- Mix the product thoroughly and apply it with a brush (with synthetic bristles) or roller. If the product is applied by spraying, it should be diluted with water up to 10% by weight.
- A single coat is sufficient to obtain full coverage. A second coat of the product can be applied 1–4 hours after the first coat.

#### USE ON INDOOR WALLS.

- Make sure that the wall is well dry then clean the surface using a dry cloth.
- Mix the product thoroughly and apply it with a brush (with synthetic bristles) or roller. If the product is applied by spraying, it should be diluted with water up to 10% by weight.
- A single coat is sufficient to obtain full coverage. A second coat of the product can be applied 1–4 hours after the first coat.



Indoor use



Ready to use



Applied by spraying,  
with a brush or roller



Tool cleaning  
with water



Coverage 10–15 m<sup>2</sup>/l  
per coat



Final drying  
24 hours

### CHEMICAL/PHYSICAL CHARACTERISTICS

Specific weight: 1.20 ± 0.05 g/ml

Brookfield viscosity: 5400 ± 500 (4/20/25)

### WARNINGS

Keep from freezing. Store at temperatures between 5°C and 35°C.

Mix well before use.

Apply at a temperature above 10°C with relative humidity below 75%; temperature and humidity influence the stated drying times.

If medical advice is needed, have a product container or label at hand.

Keep out of reach of children.

Dispose of contents and container in accordance with local, regional and international regulations.



# Technical Data Sheet

---

## NOTES

Complies with the VOC (Volatile Organic Compound) limits set by the Decopaint Directive (Directive 2004/42/EC).

---

## SAFETY RECOMMENDATIONS

Consult the product's safety data sheet (SDS), which can be downloaded from the website [www.icaforyou.com](http://www.icaforyou.com).

---

The user must first ensure the suitability of the product for the specific intended use. We accept no responsibility for the outcome of the processing operations. The information contained on this data sheet, and any verbal information that may be provided, is supplied to the best of our knowledge. No liability is accepted for obsolete or incorrect information. The information on this data sheet is rendered obsolete upon publication of a new edition. Contact us to receive the latest edition or download it from the website [www.icaforyou.com](http://www.icaforyou.com).

---