

## **1K-STUK - WATER-BASED FILLER**

Water-based solvent-free filler for indoor use and surface filling prior to coating. It boasts sandability, has limited shrinkage and good bonding to the surface.

#### COLORS

027MNS Dark walnut 027MB White 027MT Teak 027MP Pine 027MR Oak 027MN Walnut 027MD Douglas

#### INTENDED USES

General wood filling.

## APPLICATION

#### USE

- Clean the surface well.
- Apply over the flaw or defect with a spatula.
- Allow to dry at 20°C for 6-8 hours.
- Sand away any excess filler.
- Overcoating can now be done.











## CHEMICAL/PHYSICAL CHARACTERISTICS

Specific weight:  $2.01 \pm 0.05 \text{ g/ml}$ 

pH:

7 - 8

#### WARNINGS

Keep from freezing. Store at temperatures between 5°C and 35°C.

Mix well before use.

Apply at a temperature above 10°C with relative humidity below 75%; temperature and humidity influence the stated drying times.

If medical advice is needed, have a product container or label at hand.

Keep out of reach of children.

Dispose of contents and container in accordance with local, regional and international regulations.

# **Technical Data Sheet**



## NOTES

Complies with the VOC (Volatile Organic Compound) limits set by the Decopaint Directive (Directive 2004/42/EC).

### SAFETY RECOMMENDATIONS

Consult the product's safety data sheet (SDS), which can be downloaded from the website

www.icaforyou.com.

The user must first ensure the suitability of the product for the specific intended use. We accept no responsibility for the outcome of the processing operations. The information contained on this data sheet, and any verbal information that may be provided, is supplied to the best of our knowledge. No liability is accepted for obsolete or incorrect information. The information on this data sheet is rendered obsolete upon publication of a new edition. Contact us to receive the latest edition or download it from the website <u>www.icaforyou.com</u>.